YANMAR

vetus



SELECTION TABLE

VETUS EQUIPMENT FOR YANMAR ENGINES



vetus 5 WARRANTY

5PLUS WARRANTY*

2025-2026

* When a VETUS around the engine package is purchased in combination with a Yanmar engine, you will receive five years warranty on VETUS equipment. For more details please check www.vetus.com/en/5-plus-warranty

SELECTION-TABLE VETUS ENGINE INSTALLATION COMPONENTS FOR YANMAR ENGINE RANGE 9-110HP

Engine type	**1GM10**		**2YM15**		**3YM20**		**3YM30AE**		**3JH40**		**4JH45CR**		**4JH57CR**		**4JH80CR**		**4JH110CR**	
Power/max rpm	9.1hp/3600		14hp/3600		21hp/3600		29hp/3200		40hp/3000		45hp/3000		57hp/3000		80hp/3200		110hp/3200	
Gearbox ratio	2,21:1	2,62:1	2,21:1	2,62:1	2,21:1	2,62:1	2,21:1	2,62:1	2,23:1	2,64:1	2:1	2.5:1	2:1	2,47:1	2:1	2.63:1	1.97:1	2.8:1
VETUS waterlubricated sterngear systems																		
* minimum shaftdiam., duplex 1-4462	25						30			35	30	35	30	35	35	40		
VETUS manganese bronze propellers for displacement boats																		
* 3-blade, P3B, diameter in inches	12"	13"	13"	14"	14"	15"	16"	18"	18"	20"	17"	20"	18"	21"	19"	22"	on request	
*4-blade, P4E, diameter in inches	on request																	
FLEXOFOLD folding propellers *can be purchased through the Flexofold network only (please check www.flexofold.com).*																		
Flexofold 2-blade propeller	13"	14"	14"	15"	15"	16"	16"	-	-	-	-	-	-	-	-	-	-	-
Flexofold 3-blade propeller	-	-	-	15"	15"	16"	15"	16"	17"	18"	17"	18"	18"	20"	20"	22"	-	24"
Flexofold 4-blade propeller	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	20"	-
VETUS flexible couplings:																		
* Bullflex type:	n.a.		n.a.		02		04				08	04	08			12		
* Uniflex type:	13										16							
* Combiflex type:	13								12		13	12						
Adaptor flange	FLANGE1(KM2P, KM3P), FLANGE3(KM4A, KMH4A), CT50082(ZF25(A)), CT 50009(Bullflex 8/16 when TM345)																	
VETUS water strainers																		
* hose connection in diam.(mm)	14		19						25									
* water strainer, type FTR470 or FTR330:	FTR330 or 470/13		FTR330(M) or 470/19						FTR330(M) or 470/25									
* water strainer kit, type:	WKIT33013		WKIT33019						WKIT33025									
VETUS water separator/fuel filter																		
* hose connection supply/return in mm	8.3-8.3		8-8															
* water separator/fuel filter, type:	330VTEB or 75330VTEB																	
VETUS water injected exhaust systems																		
* diameter, mm	45		51						76									
* waterlock, type:	NLP(3)45(HD)/LP/LSS45		NLP(3)50(HD)/LP/LSS50						NLP(3)75(HD)/LP/LSL/LSG75									
* combi waterlock/muffler, type:	NLPH45		NLPH50						NLPH75									
* muffler, type:	MP45		MP50						MP75									
* gooseneck, type:	LT45		LT50						LT7575									
* combi muffler/gooseneck, type:	NLPG45		NLPG50						NLPG75									
* exhaust transom connection type TRC..R, PV or SV	45R/PV or SV		50R/PV or SV						TRC7590R/75P(S)V									
* breather, type ASD or AIRVENT	V or H																	
VETUS engine remote controls																		
* to be selected	SICO, SICOG, SISCO, SISCOG, RCTOPB, RCTOPBG, RCTOPS, RCTOPSG, RCTOPTS, RCTOPTSG, AFSTTOP, AFSTTOPT																	
VETUS maintenance free batteries																		
* voltage	12		12															
* starting battery, min. Ah	VESMF70		VESMF85															
* light battery, Ah.	to be selected																	
VETUS louvred air suction vents																		
* per engine, type:	1 x ASV020				2 x ASV020						2 x ASV025		2 x ASV030		2 x ASV040		2 x ASV060	

SELECTION-TABLE VETUS EQUIPMENT FOR YANMAR ENGINE RANGE 150-370HP

Engine type	4LV-150		4LV-170		4LV-195		4LV-230		4LV-250		8LV320		8LV350		8LV370	
Power/max rpm	150 hp / 3500		170 hp / 3500		195 hp / 3500		230 hp / 3800		250 hp / 3800		320 hp/3800		350 hp/3800		370 hp/3800	
Gearbox ratio	1,53:1	2,62:1	1,67:1	2,43:1	1,53:1	2,62:1	1,67:1	2,43:1	1,67:1	2,43:1	1,67:1	2,43:1	1.93:1	2,78:1	1.93:1	2,78:1
VETUS waterlubricated sterngear systems																
* minimum shaftdiam., duplex 1-4462	35	40	35	40	40	45	40	45	40	45	45	50	45	50	45	50
VETUS manganese bronze propellers for displacement boats																
* 3 or 4-blade	on request															
VETUS flexible couplings:																
* Bullflex type:	08	12	08	12	08	16	12	16	12	32	16	32	32	32	32	32
Adaptor flange	CT50009(KMH40/41A+50/51A)															
VETUS water strainers																
* hose connection in diam.(mm)	38										38					
* water strainer, type FTR:	FTR330(M) of 470//38 of FTR1320										FTR132038 (2 x SLP11/238)					
VETUS water separator/fuel filter																
* hose connection supply/return in mm	10-12										10-10					
* water separator/fuel filter, type:	(75)340VTE(P)B															
VETUS water injected exhaust systems																
* exhaust hose, diam.(mm)	102										102					
* waterlock, type:	MF/MGP/MGS/HPW															
* muffler, type:	MP100															
* goose neck, type:	LT102															
* exhaust transom connection type TRC..R, PV or SV	TC/TRC..SV															
* breather, type ASD or AIRVENT	V or H															
VETUS maintenance free batteries																
* voltage	12															
* starting battery, min. Ah	VESMF125															
* light battery, Ah.	to be selected															
VETUS louvred air suction vents																
* per engine, type:	2 x ASV030A +		2 x ASV040A +		4 x ASV050A		4 x ASV060A		2 x ASV060A +		4 x ASV080A		4 x ASV090A		2 x ASV090A +	
	2 x ASV040A		2 x ASV050A						2 x ASV070A						2 x ASV100A	

SELECTION-TABLE VETUS EQUIPMENT FOR YANMAR ENGINES RANGE 29-315HP

Engine model	3YM30		3JH 5-E		4JH 5-E		4JH 4-TE		4JH 4HTE		4JH 3-DTE		6LPA-STP2	
Power/max rpm	29hp/3600		39hp/3000		54hp/3000		75hp/3200		110hp/3200		125hp/3800		315 hp	
Gearbox ratio	2,21:1	2,62:1	2:1	2.5:1	2:1	2,47:1	2:1	2.63:1	1.97:1	2.8:1	1.97:1	2,8:1	2,04:1	2,52:1
VETUS waterlubricated sterngear systems														
* minimum shaftdiam., duplex 1-4462	25	25	25	30	30	30	30	35	35	40	35	40	45	50
VETUS manganese bronze propellers for displacement boats														
* 3-blade, P3B, diameter in inches	on request													
* 4-blade, P4E, diameter in inches	on request													
VETUS flexible couplings:														
* Bullflex type:	02	04			08				12		08	12	16	32
* Uniflex type:	13				16				n.a.		16	n.a.	n.a.	
* Combiflex, type:	13		12						n.a.					
Adaptor flange	FLANGE1(KM2P, KM3P), FLANGE3(KM4A, KMH4A), CT50082(ZF25(A)), CT 50009(Bullflex 8/16 icm TM345)												CT50009	
VETUS water strainers														
* hose connection in diam.(mm)	19		26										45	
* water strainer, type FTR470 or FTR330:	FTR330(M) or 470/19		FTR330(M) or 470/25										FTR525	
* water strainer kit, type:	WKIT33019		WKIT33025										n.a.	
VETUS water separator/fuel filter														
* hose connection supply/return in mm	8-8												9-9	
* water separator/fuel filter, type:	330VTEB or 75330VTEB												340VTEB or 75340VTEB	
VETUS water injected exhaust systems														
* exhaust hose, diam.(mm)	51		76										100	
* waterlock, type:	NLP(3)50(HD)/LP/LSS50		NLP(3)75(HD)/LP/LSL/LSG75										MF/MGP/HPW	
* combi waterlock/muffler, type:	NLPH50		NLPH75										n.a.	
* muffler, type:	MP50		MP75										MP100	
* gooseneck, type:	LT50		LT7575										LT102	
* combi muffler/gooseneck, type:	NLPG50		NLPG75										n.a.	
* exhaust transom connection type TRR, PV or SV	50R/PV or SV		TRC7590R/75P(S)V										TC/TRC..SV	
* breather, type ASD or AIRVENT	V or H													
VETUS engine remote controls														
* to be selected	SICO, SICOG, SISCO, SISCOG, RCTOPB, RCTOPBG, RCTOPS, RCTOPSG, RCTOPTS, RCTOPTSG, AFSTTOP, AFSTTOPT													
VETUS maintenance free batteries														
* voltage	12													
* starting battery, min. Ah	VESMF85												VESMF125	
* light battery, Ah.	to be selected													
VETUS louvred air suction vents														
* per engine, type:	2 x ASV020		2 x ASV020		2 x ASV030		2 x ASV040		2 x ASV060		2 x ASV070		4 x ASV080A	

SELECTION-TABLE VETUS EQUIPMENT FOR YANMAR ENGINE RANGE 400-640HP

Engine model	6LY400		6LY440		6LF485			6LF530			6LF550			6LT500			6LT580			6LT640		
Power/max rpm	400 hp/3300		440 hp/3300		485 hp / 3150			530 hp / 3150			550 hp / 3150			500 hp/2700			580 hp/2700			640 hp/2700		
Gearbox ratio	2,04:1	2,43:1	2,04:1	2,43:1	1,51/2:1	2,48:1	2,97:1	1,51:1	2/2,48:1	2,97:1	1,51:1	2/2,48:1	2,97:1	1,97:1	2,5:1	2,92:1	1,97:1	2,5:1	2,92:1	1,97:1	2,5:1	2,92:1
VETUS waterlubricated sterngear systems																						
* Minimum shaftdiam., duplex 1-4462	50	60			60		n.a.	60		n.a.	60		n.a.	60	n.a.		60	n.a.		n.a.		
VETUS manganese bronze propellers for displacement boats																						
* 4- or 5-blade	on request																					
VETUS flexible couplings:																						
* Bullflex type:	32		n.a.		32	n.a.		32	n.a.		32	n.a.		n.a.								
* Adaptor flange	KMH61A/V, ZF280(A), ZF286(A)/V, ZF305-3(A)																					
VETUS water strainers																						
* Hose connection in diam.(mm)	45				50,8									60								
* Water strainer, type FTR:	FTR132050													FTR132063								
VETUS water separator/fuel filter																						
* Hose connection supply/return in mm	12-12				10 - 10									10 - 8								
* Water separator/fuel filter, type:	(75)350VTE(P)B				(75)340VTEB																	
VETUS water injected exhaust systems																						
* Exhaust hose, diam.(mm)	127				154									150								
* Waterlock, type:	MF/MGP/MGS/HPW																					
* Muffler, type:	n.a.																					
* Goose neck, type:	LT127				LT152																	
* Exhaust transom connection type TRC..SV or TC	TRC125SV/TC125				TRC150SV/TC150																	
* Breather, type ASD or AIRVENT	V or H																					
VETUS maintenance free batteries																						
* Voltage	12				12V - 24V									24								
* Starting battery, min. Ah	VESMF165				12V: 1 x VESMF200 - 24V: 2 x VESMF125									2 x VESMF125								
* Light battery, Ah.	to be selected																					
VETUS louvred air suction vents																						
* Per engine, type:	4 x ASV100A		2 x ASV150A +		4 x ASV125			4 x ASV070			2 x ASV150			4 x ASV125			4 x ASV150			4 x ASV100		
			2 x ASV070A					2 x ASV125			2 x ASV125									2 x ASV125		